



**The Sensepoint range of flammable, toxic and oxygen gas detectors offer users a high quality, low cost solution to their industrial gas monitoring needs.**



## Fit For Purpose

- Flammable, toxic and oxygen versions available
- High performance, low cost
- Suitable for new and retro fit applications

## Proven Sensor Technology

- Surecell™ electrochemical sensors
- Poison resistant catalytic bead
- Fast and reliable
- Typical 2 to 5 years operational life

## ATEX Certified

- Complies with the latest European standards
- Hazardous area approval and performance
- IP 65/66 for use in harsh environments

## Easy to Use

- Factory set operation
- Simple to replace
- Minimal training required

## Range of Accessories

- Weatherproof cap
- Flow adaptor
- Duct mounting kit
- Collecting cone

**The Sensepoint range of flammable, toxic and oxygen gas detectors offer users a high quality, low cost solution to their industrial gas monitoring needs. Installation in potentially explosive atmospheres is made by the use of a suitable Exd or Exe approved junction box. The industry standard outputs from Sensepoint are connected to either a choice of Honeywell Analytics' controllers or 3rd party DCS/PLC systems. Both flammable and toxic versions are certified to the latest European ATEX safety and performance standards.**

The flammable detector is available in either %LEL or PPM detection range versions and provides an industry standard mV bridge output. Typical life expectancy is greater than 5 years, after which the detector is simply replaced with a new one.

The toxic detectors are supplied pre calibrated for easy installation and provide an industry standard 2 wire 4-20mA loop output. User connections are Exd, while front end Intrinsic Safety (IS) design allows for easy exchange of the replaceable sensor while powered. IS design also removes the need for a sinter enabling very fast speed of response and detection of 'sticky' gases such as Chlorine and Ammonia.

Sensepoint has proven its suitability across a wide range of demanding applications by delivering high performance and reliability at an affordable cost.




# Installation Details




## Dimensions

### Flammable %LEL or PPM Version



### Toxic or Oxygen Version



Sensepoint flammable and toxic gas detectors are installed using suitable Exd or Exe junction boxes. The standard junction box available from Honeywell Analytics includes an earth continuity plate for added RFI protection. The detectors have a choice of mounting thread size to match local preferences.

The Sensepoint range of flammable and toxic detectors are designed for use with a wide range of controllers available from Honeywell Analytics or with 3rd party control equipment accepting their industry standard output signals.


# Installation Details




## Electrical Connections

## Typical Terminal Connections


### Flammable %LEL Version




3 Wire mV Bridge Circuit




### Toxic or Oxygen Version




2 Wire 4-20mA (Sink)



### Flammable PPM Version



3 Wire mV Bridge Circuit



# Technical Specification



Gas & Range	Flammable 0-100%LEL	Flammable PPM (Typically 0-10%LEL)	Hydrogen Sulfide (H <sub>2</sub> S) 20/ 50/100ppm	Carbon Monoxide (CO) 100/200/500ppm	Ammonia (NH <sub>3</sub> ) 50/ 1000ppm	Chlorine (Cl <sub>2</sub> ) 5/15ppm	Oxygen (O <sub>2</sub> ) 25% V/V	Hydrogen (H <sub>2</sub> ) 1000/10000ppm	Sulfur Dioxide (SO <sub>2</sub> ) 15/50ppm	Nitric Oxide (NO) 100ppm	Nitrogen Dioxide (NO <sub>2</sub> ) 10ppm
<b>Operating Temp</b>	-55 to +80°C <sup>1</sup>	-30 to +65°C	-25 to +50°C	-20 to +50°C	-20 to +40°C	-20 to +50°C	-15 to +40°C				
<b>Operating Humidity</b>	Continuous: 20 to 90% RH (non-condensing). Intermittent: 10 to 99% RH (non-condensing)										
<b>Storage Conditions</b>	0 to 25°C; 30 to 70% RH		0 to 25°C; 30 to 70% RH								
<b>Operating Pressure</b>	90 to 110kPa										
<b>Warm-up Time</b>	< 10 minutes	< 20 minutes	< 3 minutes			< 5 minutes	< 3 minutes	12 hours	1 hour		
<b>Response Time</b>											
T20			< 6 secs	< 5 secs	–	< 10 secs	< 3 secs	–	–	< 3 secs	< 15 secs
T50	< 5 secs		< 15 secs	< 12 secs	< 10 secs	< 20 secs	< 5 secs	< 10 secs	< 10 secs	< 5 secs	< 30 secs
T90	< 10 secs		< 40 secs	< 30 secs	< 65 secs	< 105 secs	< 10 secs	< 45 secs	< 90 secs	< 30 secs	< 60 secs
<b>Supply</b>	200mA; 0.7W maximum		18 to 30V dc; 0.9W maximum								
<b>Signal Output</b>	mV bridge		Loop powered 4 to 20mA								
<b>Linearity</b>	< 5% fsd or ±10% of reading		< 5% fsd								
<b>Operating Life</b>	5 years (typical)		2 years (typical)		18 months (typical)		1 year (typical)	18 months (typical)			
<b>Storage Life</b>	Typically, over 5 years when in original sealed packaging		6 months.								
<b>Stability (zero)</b>											
with time*	< ±3% fsd/yr		< ±2% fsd/yr								
with temperature**	< ±1% fsd <sup>2</sup>	< ±3% fsd	< ±5% fsd		< ±6% fsd	< ±2% fsd		< ±2% fsd	< ±5% fsd		
with humidity	< ±1% fsd		< ±10% fsd	< ±2% fsd	< ±10% fsd	< ±2% fsd		< ±2% fsd	< ±10% fsd		
<b>Stability (span)</b>											
with time*	< ±3% fsd/yr		< ±2% fsd/yr	< ±4% fsd/yr	< ±20% fsd/yr	< 10% fsd/yr	< ±20% fsd/yr	< ±2% fsd/yr			
with temperature***	< ±3% fsd	< ±8% fsd	< ±25% fsd	< ±20% fsd	< ±20% fsd	< 40% fsd	< ±10% fsd	< ±60% fsd	< ±15% fsd	< ±25% fsd	
with humidity	< ±2% fsd		< ±10% fsd	< ±2% fsd	< ±10% fsd	< ±2% fsd	< ±1% fsd	< ±2% fsd	< ±10% fsd		
<b>Weight</b>	190g		185g			205g	185g0				
<b>Construc. Materials</b>	Polyphenylene sulfide (PPS)										
<b>I.P. (NEMA) Rating</b>	IP65 (standard), IP67 (with weather protection fitted)										
<b>Certification Details (ATEX)</b>	Ex II 2 GD EEx d IIC T6 (Tamb = -55°C to +55°C) T5 (Tamb = -55°C to +70°C) <sup>3</sup> BAS98ATEX2156X/4 SIRA03ATEX1116X (Performance)		Ex II 2 GD EEx dia IIC T4 (Tamb = -55°C to +65°C) BAS90ATEX2157X/5								
<b>Other Certifications</b>	Australian: SAA, Russian: GOST										
<b>Applicable Standards</b>	This product complies with the relevant CE standards including: EMC to EN50270, Flammable to EN50054/57, Toxic to EN445544 (H <sub>2</sub> S only)										

## NOTES

<sup>1</sup> High temp range version available -55 to +150°C – See separate datasheet DS0303

<sup>2</sup> Over temp range -20 to +55°C

<sup>3</sup> LEL version T4 -55 to +80°C, T3 -55 to +150°C

\* = % of range (fsd) per year

\*\* Over operating temperature range

\*\*\* = % of applied concentration

## Ordering Information

### Accessories

00780-A-0100	Term Hsg – Bartec DE1155 With Continuity Plate 1 x 25mm – 3 x 20mm Entries – ATEX Approved
00780-A-0160	Right Angle Mounting Bracket For Ceiling Mounting
02000-A-1635	Series 2000 Weather Housing Use With Toxic Sensor
02000-A-1640	Series 2000 Weather Housing Use With Flammable Sensor
02000-A-1642	Series 2000 Collecting Cone Use With Flammable Sensor
02000-A-1645	Series 2000 Calibration Flow Housing Assembly (Flam & Toxic)
02000-A-3120	Series 2000 Flow Housing Assembly Plastic
2106B1110	Catalytic Bridge To 4-20mA Converter
2106B2114	Toxic Calibration Kit including calibration cover, removal tool, potentiometer adjustment tool
2106D2055	M36/M40 thread adaptor
225-262-138	Cable gland and caps, 20mm, Nylon

### Spares

2106B1545	O <sub>2</sub> Electrochemical Cell Exchange Kit
2106B1546	SO <sub>2</sub> Electrochemical Cell Exchange Kit
2106B1547	Cl <sub>2</sub> Electrochemical Cell Exchange Kit
2106B1548	CO Electrochemical Cell Exchange Kit
2106B1549	H <sub>2</sub> S Electrochemical Cell Exchange Kit
2106B1594	NO Electrochemical Cell Exchange Kit
2106B1595	NH <sub>3</sub> 0-1000ppm Electrochemical Cell Exchange Kit
2106B1596	NH <sub>3</sub> 0-50ppm Electrochemical Cell Exchange Kit
2106B1597	H <sub>2</sub> 0-1000ppm Electrochemical Cell Exchange Kit
2106B1598	H <sub>2</sub> 0-10000ppm Electrochemical Exchange Kit
2106B1599	NO <sub>2</sub> 0-10ppm Electrochemical Exchange Kit

### Calibration Equipment

Contact your local Honeywell Analytics representative for details of suitable calibration equipment

### Find out more

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)

### Contact Honeywell Analytics:

#### Europe, Middle East, Africa

Life Safety Distribution AG  
Wilstrasse 11-U31  
CH-8610 Uster  
Switzerland  
Tel: +41 (0)44 943 4300  
Fax: +41 (0)44 943 4398  
[gasdetection@honeywell.com](mailto:gasdetection@honeywell.com)

#### Americas

Honeywell Analytics Distribution, Inc.  
405 Barclay Blvd.  
Lincolnshire, IL 60069  
USA  
Tel: +1 847 955 8200  
Toll free: +1 800 538 0363  
Fax: +1 847 955 8208  
[detectgas@honeywell.com](mailto:detectgas@honeywell.com)

#### Asia Pacific

Honeywell Analytics Asia Pacific  
#508, Kolon Science Valley (1)  
187-10 Guro-Dong, Guro-Gu  
Seoul, 152-050,  
Korea  
Tel: +82 (0)2 2025 0307  
Fax: +82 (0)2 2025 0329  
[analytics.ap@honeywell.com](mailto:analytics.ap@honeywell.com)

#### Technical Services

[ha.emea.service@honeywell.com](mailto:ha.emea.service@honeywell.com)

[www.honeywell.com](http://www.honeywell.com)

### Sensepoint Combustible

2106B1200	Sensepoint 0-100% LEL Flammable Sensor M20
2106B1201	Sensepoint 0-100% LEL Flammable Sensor M25
2106B1202	Sensepoint 0-100% LEL Flammable Sensor M26
2106B1203	Sensepoint 0-100% LEL Flammable Sensor M26 (VQ1AB pellistor)
2106B1204	Sensepoint 0-100% LEL Flammable Sensor 3/4NPT
2106B1205	Sensepoint ppm (0-10% LEL) Flammable Sensor M20
2106B1209	Sensepoint ppm (0-10%LEL) Flammable Sensor 3/4NPT

### Sensepoint Toxic

2106B1400	Sensepoint Hydrogen Sulfide (H <sub>2</sub> S) 0-20ppm Toxic Sensor M20
2106B1401	Sensepoint Hydrogen Sulfide (H <sub>2</sub> S) 0-50ppm Toxic Sensor M20
2106B1402	Sensepoint Hydrogen Sulfide (H <sub>2</sub> S) 0-100ppm Toxic Sensor M20
2106B1700	Sensepoint Hydrogen Sulfide (H <sub>2</sub> S) 0-20ppm Toxic Sensor 3/4NPT
2106B1701	Sensepoint Hydrogen Sulfide (H <sub>2</sub> S) 0-50ppm Toxic Sensor 3/4NPT
2106B1702	Sensepoint Hydrogen Sulfide (H <sub>2</sub> S) 0-20ppm Toxic Sensor 3/4NPT
2106B1405	Sensepoint Carbon Monoxide (CO) 0-100ppm Toxic Sensor M20
2106B1406	Sensepoint Carbon Monoxide (CO) 0-200ppm Toxic Sensor M20
2106B1407	Sensepoint Carbon Monoxide (CO) 0-500ppm Toxic Sensor M20
2106B1705	Sensepoint Carbon Monoxide (CO) 0-100ppm Toxic Sensor 3/4NPT
2106B1706	Sensepoint Carbon Monoxide (CO) 0-200ppm Toxic Sensor 3/4NPT
2106B1707	Sensepoint Carbon Monoxide (CO) 0-500ppm Toxic Sensor 3/4NPT
2106B1410	Sensepoint Chlorine (Cl <sub>2</sub> ) 0-5ppm Toxic Sensor M20
2106B1411	Sensepoint Chlorine (Cl <sub>2</sub> ) 0-15ppm Toxic Sensor M20
2106B1711	Sensepoint Chlorine (Cl <sub>2</sub> ) 0-15ppm Toxic Sensor 3/4NPT
2106B1413	Sensepoint Ammonia (NH <sub>3</sub> ) 0-50ppm Toxic Sensor M20
2106B1414	Sensepoint Ammonia (NH <sub>3</sub> ) 0-1000ppm Toxic Sensor M20
2106B1415	Sensepoint Ammonia (NH <sub>3</sub> ) 0-100ppm Toxic Sensor M20
2106B1713	Sensepoint Ammonia (NH <sub>3</sub> ) 0-50ppm Toxic Sensor 3/4NPT
2106B1714	Sensepoint Ammonia (NH <sub>3</sub> ) 0-1000ppm Toxic Sensor 3/4NPT
2106B1715	Sensepoint Ammonia (NH <sub>3</sub> ) 0-100ppm Toxic Sensor 3/4NPT
2106B1416	Sensepoint Hydrogen (H <sub>2</sub> ) 0-1000ppm Toxic Sensor M20
2106B1417	Sensepoint Hydrogen (H <sub>2</sub> ) 0-10000ppm Toxic Sensor M20
2106B1716	Sensepoint Hydrogen (H <sub>2</sub> ) 0-1000ppm Toxic Sensor 3/4NPT
2106B1717	Sensepoint Hydrogen (H <sub>2</sub> ) 0-10000ppm Toxic Sensor 3/4NPT
2106B1418	Sensepoint Nitric Oxide (NO) 0-100ppm Toxic Sensor M20
2106B1718	Sensepoint Nitric Oxide (NO) 0-100ppm Toxic Sensor 3/4NPT
2106B1420	Sensepoint Sulfur Dioxide (SO <sub>2</sub> ) 0-15ppm Toxic Sensor M20
2106B1421	Sensepoint Sulfur Dioxide (SO <sub>2</sub> ) 0-50ppm Toxic Sensor M20
2106B1720	Sensepoint Sulfur Dioxide (SO <sub>2</sub> ) 0-15ppm Toxic Sensor 3/4NPT
2106B1721	Sensepoint Sulfur Dioxide (SO <sub>2</sub> ) 0-50ppm Toxic Sensor 3/4NPT
2106B1422	Sensepoint Nitrogen Dioxide (NO <sub>2</sub> ) 0-10ppm Toxic Sensor M20
2106B1722	Sensepoint Nitrogen Dioxide (NO <sub>2</sub> ) 0-10ppm Toxic Sensor 3/4NPT
2106B1430	Sensepoint Oxygen (O <sub>2</sub> ) 25% V/V Toxic Sensor M20
2106B1730	Sensepoint Oxygen (O <sub>2</sub> ) 25% V/V Toxic Sensor 3/4NPT

#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

H\_Sensepoint\_DS0326\_V4\_EMEA  
09/07

© 2007 Honeywell Analytics

# Honeywell