



IP7130

Fixed Network Camera

Tamper Detection • Dual Streams • PoE

VIVOTEK's IP7130 fixed network camera is an economical and easy-to-use surveillance system designed for indoor applications such as offices, banks, and retail stores.

This camera comes with the tamper detection feature, which detects data loss from camera tampering in real-time. When the camera is blocked, redirected, or spray-painted, security staff will be alerted immediately in accordance with the camera settings. With its dual-stream feature, the IP7130 also allows two video streams to be delivered in a different resolutions, frame rates, and image qualities for individual recording or bandwidth demands. Images can be displayed in VGA format for real-time monitoring while displayed on a 3GPP mobile phone in lower resolution, giving users a higher level of flexibility for dealing with camera images on different platforms. The integrated 802.3af compliant PoE function reduces cabling clutter, making IP7130 a cost-effective surveillance system.

With other advanced features such as two-way audio via SIP protocol, digital I/O, HTTPS encryption, and the included 32-CH central management software, IP7130 is the camera of choice for customers requiring value in their investment.

Features

- > 1/4" CMOS Sensor in VGA Resolution
- > Real-time MPEG-4 and MJPEG Compression (Dual Codec)
- > Dual Streams Simultaneously
- > Detects Tampering from Blockage, Redirection or Spray-painting
- > 3GPP Mobile Surveillance
- > Built-in 802.3af Compliant PoE
- > Two-way Audio via SIP Protocol
- > Digital I/O for External Sensor and Alarm
- > HTTPS Encrypted Data Transmission
- > Includes Free Standard 32-CH ST7501 Central Management Software

System	<ul style="list-style-type: none"> CPU: Mozart 120 SoC Flash: 8MB RAM: 64MB + 64MB Embedded OS: Linux 2.6 	Viewing System Requirements	<ul style="list-style-type: none"> OS: Microsoft Windows 2000/XP/Vista Browser: Mozilla Firefox, Internet Explorer 6.x or above Cell phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.5 or above
Lens	<ul style="list-style-type: none"> CS-mount, f = 4.0 mm, F1.6, Fixed 	Installation, Management, and Maintenance	<ul style="list-style-type: none"> Installation Wizard 2 32-CH ST7501 central management software Supports firmware upgrade
Angle of View	<ul style="list-style-type: none"> 71° (horizontal) 	Applications	<ul style="list-style-type: none"> SDK available for application development and system integration
Shutter Time	<ul style="list-style-type: none"> 1/5 sec. to 1/15,000 sec. 	Warranty	<ul style="list-style-type: none"> 12 months
Image Sensor	<ul style="list-style-type: none"> 1/4" CMOS sensor in VGA resolution 	<div style="text-align: center; background-color: #0056b3; color: white; padding: 5px; font-weight: bold;">System Overview</div>	

All specifications are subject to change without notice. Copyright ©2009 VIVOTEK INC. All rights reserved.

Distributed by:

6F, No.192, Lien-Cheng Rd., Chung-Ho, Taipei County, Taiwan
 Tel: +886 2 8245 5282 | Fax: +886 2 8245 5532 | E-mail: sales@vivotek.com
VIVOTEK USA, INC.
 470 Lakeside Drive Suite C, Sunnyvale, CA 94085 USA
 Tel: 408-773-8686 | Fax: 408-773-8298 | E-mail: salesusa@vivotek.com